






01



Position of engine stay attachment points.

| | | | | | | | | | | |
|------------------|---|---|---|---|---|---|---|-------|-------|-------|
| Engine stay type | 1 | 2 | 3 | 4 | 5 | 6 | 7 | TOTAL | Y | Z |
| CASE1 | ⑤ | ⑥ | ⑥ | ⑥ | ⑥ | ⑥ | ⑥ | 5 | ⑦=175 | ⑦=244 |
| CASE2 | ⑥ | ⑥ | ⑥ | ⑥ | ⑥ | ⑥ | ⑥ | 6 | ⑧=250 | ⑧=260 |
| CASE3 | ⑧ | ⑧ | ⑧ | ⑧ | ⑧ | ⑧ | ⑧ | 6 | | |

| REVISIONS | | NO. | DESCRIPTION | (DATE) | ZONE | AP. | CHK. |
|-----------|---|-----|-------------|------------|-------|-----|------|
| 1 | ① | 1 | ① | 2014-01-21 | D,E-1 | 吉川 | 田中 |
| 2 | ② | 2 | ② | 2014-05-20 | 全面 | 江戸 | 吉川 |
| 3 | ③ | 3 | ③ | 2014-07-16 | 全面 | 江戸 | 吉川 |
| 4 | ④ | 4 | ④ | 2017-10-17 | 全面 | 青田 | 田中 |



- 備考
- 次のものは、仕様範囲に含まれません。
 - (A) 上部格子用外側支柱及び取手
 - (B) 梯子 (フロア) 上部格子及び、下部格子 上部格子間
 - 敷板 上部ボツ側 T.6
それ以外 T.4, 5

- Remarks
- Following shall be supplied by the shipbuilder.
 - (A) Handrail and props on upper platform
 - (B) Large stairs between upper- and middle- and lower-platforms.
 - Plate thickness of platform
 - Upper platform (pump side) t=6
 - Upper platform (exhaustside) t=4.5
 - Lower platform

基本図

| COMMON VARIATION OF TOLERANCE (M.M.) | RATINGS OF NOMINAL DIMENSION | OVER 0.1 TO 0.3 | OVER 0.3 TO 0.5 | OVER 0.5 TO 0.8 | OVER 0.8 TO 1.2 |
|--------------------------------------|------------------------------|-----------------|-----------------|-----------------|-----------------|
| TOLERANCE | | +0.1 | +0.2 | +0.3 | +0.5 |

ACAD